


**COMPOSITION**

TOP		
<b>Conveying surface</b>	Material	PVC
	thickness	0.8 MM
	Surface pattern	SMOOTH
	Colour	PETROL GREEN
	Hardness	80 Shore A
<b>Textile carcass</b>	Material	POLYESTER (PET)
	Piles no.	2
	Weft type	RIGID
BOTTOM		
<b>Driving surface</b>	Material	FABRIC
	Thickness	--
	Surface pattern	FABRIC
	Colour	WHITE


**TECHNICAL SPECIFICATIONS**

<b>Total thickness</b>	2.5 MM	
<b>Weight</b>	3.1 KG/M <sup>2</sup>	
<b>Elongation at 1%</b>	10 N/mm	
<b>Breacking load</b>	140 N/mm	
<b>Temperature resistance</b>	min. -10 °C / max. +80 °C Using of the belt with limit values may reduce its service life.	
<b>Minimum radius / diameter</b>	Knife edge minimum radius	--
	Bending roller min. diameter	45 MM
	Counter-bending roller min. Diameter	55 MM
<b>Coefficient of friction on driving surface</b>	Steel sheet	0,18
	Laminated plastic/wood	0,20
	Steel roller	0,18
	Rubberized roller	0,25
<b>Max. Production width</b>	3000 MM	

**FEATURES**

<b>Humidity influence</b>	NO
<b>Suitable to metal detector</b>	NO
<b>Conveying on skid bed</b>	YES
<b>Conveying on rollers</b>	YES
<b>Inclined conveying</b>	NO
<b>Curved conveyor</b>	NO
<b>Chemical resistances</b>	NO
<b>Oil and fat resistance</b>	YES
<b>Food grade</b>	NO
<b>Antistatic AS</b>	YES

**JOINT METHOD**

SINGLE FINGER 80*10 or 80*15
DOUBLE FINGER 50*20
OVERLAP JOINT
DIAGONAL FINGER
MECHANICAL FASTENER

**SUITABLE FOR**

GENERAL PURPOSE OF LIGHT DUTY CONVEYING SYSTEM

**JOINTING PRESS SETTINGS**

UPPER PLATEN TEMP. 175 °C  
 BOTTOM PLATEN TEMP. 175 °C  
 CURING TIME 3 MIN  
 PRESSURE 1.5 BAR

**DISCLAIMER**

The specifications and values mentioned in the technical data sheet are drawn from the laboratory department of the company's factory, and Righa for Trading and Manufacturing SL (RIGALLI) is not responsible for any change or modification of these values or specifications.