

Model No. PU/ARENA/NP/1.9-2 AUTO LUBRICANT

COMPOSITION

Top Conveying surface	Material	PU
	Thickness	0.7 mm
	Surface pattern	Arena Sand
	Colour	Black
	Hardness	92 Shore A
Textile carcass	Material	Polyster (PET)
	Piles no.	2
	Weft type	Rigid
Bottom Driving surface	Material	Auto Lubricante
	Thickness	- mm
	Surface pattern	Fabric
	Colour	Grey

TECHNICAL SPECIFICATIONS

Total thickness	1.9	mm
Weight	2.0	kg/m ²
Elongation at 1%	10	N/mm
Breaking load	140	N/mm
Temperature resistance	min.	-10 °C
	max.	+80 °C

*Use of the belt with limit values may reduce its life.

● Minimum radius / diameter Pol Vester (Pet)

Knife edge minimum radius	-
Bending roller min. diameter	30 mm
Counter-bending roller min. Diameter	50 mm

● Coefficient of friction on driving surface

Steel sheet	0.18
Laminated plastic/wood	0.20
Steel roller	0.18
Rubberized roller	0.25

● Max. Production width


3000 mm

SUITABLE FOR

General purpose of light duty conveying system.
Treadmill.
Logistics application.

> Technical data sheet

- Industrial application
- Sport application



TECHNICAL SPECIFICATIONS

Humidity influence	Limited
Suitable to metal detector	No
Conveying on skid bed	Yes
Conveying on rollers	Yes
Inclined conveying	No
Troughed application	No
Flame retardant	No
Curved conveyor	No
Chemical resistances	Yes
Oil and fat resistance	Yes
Food grade	No
Antistatic AS	Yes

JOINT METHOD

Single finger
Diagonal finger
Mechanical fastener

TECHNICAL SPECIFICATIONS

Upper platen temp	162 °C
Bottom platen temp	162 °C
Curing time	3 Min
Pressure	1.5 Bar

DISCLAIMER

The specifications and values mentioned in the technical data sheet are drawn from the laboratory department of the company's factory, and Righa for Trading and Manufacturing SLU (RIGALLI) is not responsible for any change or modification of these values or specifications.