

**Model No.** PVC/PO/NA/2.0-2

## COMPOSITION

Top Conveying surface	Material	IMPREGNATION FABRIC
	Thickness	- mm
	Surface pattern	Fabric
	Colour	Orange
	Hadness	-
Middle	Material	Orange PVC
	Piles no.	2
	Weft type	Rigid
Bottom Driving surface	Material	Impregnation Fabric
	Thickness	- mm
	Surface pattern	Fabric
	Colour	Orange

## TECHNICAL SPECIFICATIONS

Total thickness	2.0	mm
Weight	2.0	kg/m <sup>2</sup>
Elongation at 1%	10	N/mm
Breacking load	140	N/mm
Temperature resistance	min.	-10 °C
	max.	+90 °C

\*Use of the belt with limit values may reduce its life.

### ● Minimum radius / diameter Pol Vester (Pet)

Knife edge minimum radius	-
Bending roller min. diameter	40 mm
Counter-bending roller min. Diameter	40 mm

### ● Coefficient of friction on driving surface

Steel sheet	0.18
Laminated plastic/wood	0.20
Steel roller	0.18
Rubberized roller	0.25

### ● Max. Production width




3000 mm

## SUITABLE FOR

General purpose of light duty conveying system.  
Dock shelter and fast doors applicator.

## > Technical data sheet

• Industrial application



## TECHNICAL SPECIFICATIONS

Humidity influence	No
Suitable to metal detector	No
Conveying on skid bed	Yes
Conveying on rollers	Yes
Inclined conveying	No
Troughed application	No
Flame retardant	No
Curved conveyor	No
Chemical resistances	Limited
Oil and fat resistance	Limited
Food grade	Consalt
Antistatic AS	Yes

## JOINT METHOD

Single finger	Diagonal finger Mechanical fastener
Double Finger	
Overlap Joint	

## TECHNICAL SPECIFICATIONS

Upper platen temp	175 °C
Bottom platen temp	175 °C
Curing time	3 Min
Pressure	1.5 Bar

## DISCLAIMER

The specifications and values mentioned in the technical data sheet are drawn from the laboratory department of the company's factory, and Righa for Trading and Manufacturing SLU (RIGALLI) is not responsible for any change or modification of these values or specifications.