

Model No. ZETUN GREEN

COMPOSITION

Top Conveying surface	Material	PVC
	Thickness	0.6 mm
	Surface pattern	Smooth
	Colour	Light Neon Green
	Hardness	65 Shore A
Textile carcass	Material	Polyester (PET)
	Piles no.	3
	Weft type	Flexible
Bottom Driving surface	Material	Small Diamond
	Thickness	0.8 mm
	Surface pattern	Small Diamond
	Colour	Light Neon Green

TECHNICAL SPECIFICATIONS

Total thickness	4.9	mm
Weight	4.9	kg/m ²
Elongation at 1%	18	N/mm
Breaking load	210	N/mm
Temperature resistance	min.	-10 °C
	max.	+80 °C

*Use of the belt with limit values may reduce its life.

● Minimum radius / diameter Pol Vester (Pet)

Knife edge minimum radius	-
Bending roller min. diameter	100 mm
Counter-bending roller min. Diameter	140 mm

● Coefficient of friction on driving surface

Steel sheet	0.25
Laminated plastic/wood	0.22
Steel roller	0.25
Rubberized roller	0.30

● Max. Production width




3000 mm

SUITABLE FOR

General purpose of light and heavy duty conveying system. Specifically developed by Rigalli for olives industry.

> Technical data sheet

- Food application



TECHNICAL SPECIFICATIONS

Humidity influence	Yes
Suitable to metal detector	No
Conveying on skid bed	No
Conveying on rollers	Yes
Inclined conveying	No
Troughed application	Yes
Flame retardant	No
Curved conveyor	No
Chemical resistances	Limited
Oil and fat resistance	Yes
Food grade	Yes
Antistatic AS	Yes

JOINT METHOD

Single finger Double Finger Diagonal finger	Mechanical fastener
---	---------------------

TECHNICAL SPECIFICATIONS

Upper platen temp	175 °C
Bottom platen temp	175 °C
Curing time	3 Min
Pressure	1.5 Bar

DISCLAIMER

The specifications and values mentioned in the technical data sheet are drawn from the laboratory department of the company's factory, and Righa for Trading and Manufacturing SLU (RIGALLI) is not responsible for any change or modification of these values or specifications.